



TECHNICAL DATA SHEET

CPP 0122 – 2K FADE OUT THINNER

DESCRIPTION

2K FADE OUT THINNER is a top quality, thinner designed for use in local spot repairs on hard factory baked finishes and hardened 2 pack finishes.

2K FADE OUT THINNER can be used with many 2K topcoats including solid colours, non-basecoat metallic and 2K clear lacquers. Where a fade-out thinner is required.

MIXING

Mix 2K clear lacquer in the correct ratio with the appropriate 2K hardener. Then mix approximately 4 parts 2K FADE OUT THINNER: 1 part of this ACTIVATED CLEAR LACQUER by volume.

GUN SETUP

Compliant spray gun.

FLASH POINT

32°C – 55°C

STORAGE

Unmixed correctly stored material, in firmly closed original contains, has a shelf life of over a year. Contents of opened containers should be used up quickly.

HEALTH & SAFETY

Please refer to relevant Health and Safety Data Sheet, reference no. HSD 0122.

NOTE

This data relates only to the product designated herein and does not apply to use in combination with any other materials or in any other process.

The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.

Our product range is under continuous development and therefore products and specifications are subject to change without notice.

This product is for professional use only.

All trademarks, registered trademarks, brands and product names respected.

Churchill Paints Ltd.

Riverdane Rd, Eaton Bank Trading Estate, Congleton, Cheshire, United Kingdom

T: +44 (0)1260 290 666

F: +44 (0)1260 290 444

✉: sales@churchill-paints.co.uk

Website: <http://www.churchill-paints.com>

© CHURCHILL PAINTS 1994