

Date of issue: 27/11/2002

Edition: 4

Product and reference: 36040000100 / F-714 SHOP PRIMER

SAFETY DATA SHEET**1. IDENTIFICATION OF THE PREPARATION AND COMPANY**

Identification of the company: Bernardo Ecenarro, S.A.
 Poligono Industrial San Lorenzo
 20870 ELGOIBAR (Guipuzcoa) ESPAÑA
 Tlf: +34 943742800 Fax: +34 943740603

Product's Description:

Code: 36040000100

Name : F-714 SHOP

Intended use: Primer for diverse types of surfaces.

Beige 1639, Cream 1749, Oxide Red 8072, Black 9005

2. COMPOSITION / INFORMATION ON INGREDIENTS

Substances presenting a health hazard according to Directive 67/548/EEC and later adoptions and modifications:

<u>CEE No.</u>	<u>Name</u>	<u>Conc. range</u>	<u>R-Phrases(*)</u>	<u>Symbol</u>
024-007-00-3	ZINC CHROMATES	1.0 - 2.5 %	R45 R22 R43 R50/53	T, N
601-022-00-9	XYLENE (mixed isomers)	10 - 25 %	R20/21 R38 R10	Xn
603-004-00-6	N-BUTANOL	25 - 50 %	R22 R41 R37/38 R67 R10	Xn
601-021-00-3	TOLUENE	10 - 25 %	R20 R11	F, Xn
601-023-00-4	ETHYLBENZENE	2.5 - 10 %	R20 R11	F, Xn
606-002-00-3	BUTANONE	10 - 25 %	R36 R66 R67 R11	F, Xi
604-001-00-2	PHENOL	< 1 %	R24/25 R34	T

*For full text see section 16.

3. HAZARDS IDENTIFICATION

Highly flammable. Toxic.

Contains cancerogenic substances.

Product is flammable because of its composition in solvents.

4. FIRST AID MEASURES**General:**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation:

Remove to fresh air, keep the patient warm and rest. If breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in the recovery position and seek medical advice.

Eye contact:

Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart, and seek medical advice.

Skin contact:

Remove contaminated cloth. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners.

Ingestion:

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

5. FIRE FIGHTING MEASURES.**Extinguishing media:**Recommended: alcohol resistant foam, CO₂, powder, water spray/mist.

not to be used: water jet.

Date of issue: 27/11/2002

Edition: 4

Product and reference: 36040000100 / F-714 SHOP PRIMER**Recommendations:**

Fire will produce dense black smoke containing hazardous substances of combustion. Exposure to decomposition products may be a hazard to health. Appropriate self-contained breathing equipment may be required. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

Exclude sources of ignition and ventilate the area. Exclude non-essential personnel. Avoid breathing vapours and contact with skin and eyes. Refer to protective measures listed in Sections 7 and 8. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with the local waste regulations (see Section 13). Do not allow to enter drains or water courses.

Clean preferably with a detergent; avoid the use of solvents.

If the product enters drains or sewers the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the National Rivers Authority.

7. HANDLING AND STORAGE**Handling**

Vapours are heavier than air and may spread along floors. They may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the work exposure limits.

Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Keep the container tightly closed.

Exclude sources of heat and open flame. Non-sparking tools should be used.

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist.

Smoking, eating and drinking should be prohibited in areas of storage and use.

For personal protection, see Section 8.

Never use pressure to empty: the container is not resistant to pressure.

Always keep in containers made of the same material as the supply container.

When the operatives are inside the spray booth, applying or not, and ventilation is not sufficient to control particles and solvent vapour concentrations, air-fed respiratory protective equipment should be worn, until the concentrations mentioned are below the work exposure limits.

Avoid the inhalation of dusts, particles, and spray mists arising from the use of this zinc chromate containing product.

Also avoid the inhalation of dusts, particles, and smoke arising from the treatment of painted surfaces during sanding, polishing and other works which require heat, welding, cut, etc.

Storage

Storage in accordance with the legal procedures for chemical products.

Observe the label precautions. Store between 5 and 30 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Containers which are opened should be properly resealed and kept in a upright position to prevent leakage. The principles contained in the HSE's guidance note Storage and Packaged Dangerous Substances should be observed when storing this product. Store separately from oxidising agents and strongly alkaline and strongly acidic materials, amines, alcohol and water.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Engineering Measures**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn. (see 'Personal protection' below)

EXPOSURE LIMITS (ACGIH 1996)

TLV: Threshold Limit Value

TWA: Time Weighted Average

STEL: Short Term Exposure Limit

CAS No.	Name	TLV-TWA		TLV-STEL	
		(ppm)	(mg/m3)	(ppm)	(mg/m3)
13530-65-9	ZINC CHROMATES	(Cr)	0,01-A1		
1330-20-7	XYLENE (mixed isomers)	100	434	150	651

Date of issue: 27/11/2002

Edition: 4

Product and reference: 36040000100 / F-714 SHOP PRIMER

71-36-3	N-BUTANOL			(c50-D)	(c152-D)
108-88-3	TOLUENE	50-D	188-D		
100-41-4	ETHYLBENZENE	100	434	125	543
78-93-3	BUTANONE	200	590	300	885
108-95-2	PHENOL	5-D	19-D		

() Adapted data for which modification is proposed.

c - Indicates a Maximum Exposure.

D - Indicates a risk of absorption through the skin.

A1 - Human confirmed carcinogenic

Personal protection

All ppe, including rpe, used to control exposure to hazardous substances must be selected to meet requirements of the COSHH Regulations.

Respiratory protection:

Air-fed respiratory protective equipment should be worn when this product is sprayed. This should be in addition to other measures taken to reduce exposure (e.g. in booth design and operation and process modifications). Non-essential and unprotected people should be excluded from the area if exposure is possible.

Hand protection:

When skin exposure may occur, advice should be sought from glove suppliers on appropriate types.

	Recommended gloves	Alternative gloves
Alcohol	Neoprene rubber	Nitril rubber
Glycol ester	Butyl rubber	Neoprene rubber
Halogen	Polyvinyl Alcohol	Nitril rubber
Ketone	Polyvinyl Alcohol	Latex rubber
Aliphatic hydrocarbons	Neoprene rubber	Nitril rubber
Aromatic hydrocarbons	Polyvinyl Alcohol	Nitril rubber
Esters	Polyvinyl Alcohol	Neoprene rubber
Ethers	Polyvinyl Alcohol	Nitril rubber

Barrier creams may help to protect exposed areas of the skin but are not substitutes for full physical protection. They should not be applied once exposure has occurred.

Eye protection:

Eye protection (e.g. glasses) designed to protect against liquid splashes should be worn.

Skin protection:

Anti-static cotton or cotton/synthetic overalls which are resistant to high temperatures are suitable.

Grossly contaminated cloth should be removed and the skin washed with soap and water or a proprietary skin cleaner.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Viscous liquid	
Boiling point (°C):	> 35 °C	
Flash point: (°C):	< 0 °C	Method: Closed cup
Vapour density:	heavier than air	
Vapour explosion limit:	0,8 %	
Solubility in water:	Partially miscible	
pH:		
Density:	1,00± 0,06	

10. STABILITY AND REACTIVITY

Stable under the recommended storage and handling conditions. (See section 7). In case of fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide and oxides of nitrogen may be produced.

Keep away from oxidising agents and strongly alkaline and strongly acidic materials to prevent the possibility of exothermic reaction.

Date of issue: 27/11/2002

Edition: 4

Product and reference: 36040000100 / F-714 SHOP PRIMER

11. TOXICOLOGICAL INFORMATION

There is no data available on special product-tests.

Exposure to organic solvent vapours above work exposure limits may result in adverse health effects such as irritation of the mucous membrane and the respiratory system and adverse effects on the kidneys, liver and central nervous systems. Symptoms can be headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, consciousness.

Repeated or prolonged contact with the product may result in removal of natural grease from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in the eyes may cause irritation and reversible local damage.

Zinc chromate is a recognised human carcinogen and there is evidence that exposure can result in lung cancer. There is no evidence of a similar risk arising from the use of coatings containing this pigment.

Irritating preparation. Inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. There may also occur severe respiratory difficulties, stimulation of the central nervous system and in extreme cases unconsciousness.

Irritating preparation. Prolonged or repeated contact with the skin or mucous membranes may result in irritant symptoms such as redness, blistering or dermatitis. Onset of symptoms may be delayed. Cases of allergic skin reactions have been observed.

12. ECOLOGICAL INFORMATION

There is no data available on special product-tests.

The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

The product could contain a substance harmful or toxic for the environment. In this sense, check and see sections 2 and 16 following the R-phrases.

13. DISPOSAL CONSIDERATIONS

Do not allow into drains or water courses or dispose of where ground or surface waters may be affected.

It can be burned in appropriate installation, respecting the waste regulation of the local authorities.

Regarding packaging, please refer to Directive 94/62 DOCE L 365 of 31/12/94.

14. TRANSPORT INFORMATION

Proper Shipping Name: Flammable liquid, toxic, n.o.s., (ZINC CHROMATES; TOLUENE)

UN no:1992 Packing Group: II

Road/rail (ADR - RID)

Class: 3 Classification Code: FT1 Label: 3+6.1

Sea (IMDG)

Class: 3 Marine Pollutant: 0 Label: 3+6.1
EmS: 3-07 MFAG: 300,306

Air (ICAO-IATA)

Class: 3 Label: 3+6.1

15. REGULATORY INFORMATION

Under the terms of Directive 88/379/EEC and later adoptions and modifications, the product is labelled as follows:

Harzard Symbols: (F) HIGHLY FLAMMABLE, (T) TOXIC, (N) DANGEROUS FOR THE ENVIRONMENT

Contains:

N-BUTANOL
XYLENE (mixed isomers)
TOLUENE
ZINC CHROMATES

R-Phrases:

R45.- May cause cancer.

R20/21/22.- Also harmful by inhalation, in contact with skin and if swallowed.

R41.- Risk of serious damage to eyes.

R43.- May cause sensitization by skin contact.

R51/53.- Toxic to aquatic organisms, may cause long-term adverse affects in the aquatic environment.

Date of issue: 27/11/2002

Edition: 4

Product and reference: 36040000100 / F-714 SHOP PRIMER

R11.- Highly flammable.

S-Phrases:

S53.- Avoid exposure - obtain special instructions before use.

S45.- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S38.- In case of insufficient ventilation, wear suitable respiratory equipment.

S23.- Do not breathe vapour.

S29.- Do not empty into drains.

S60.- This material and/or its container must be disposed of as hazardous waste.

Other Phrases:

Restricted to professional users.

16. OTHER INFORMATION

Complete text of R-phrases listed in Section 2:

R45.- May cause cancer.

R22.- Also harmful if swallowed.

R43.- May cause sensitization by skin contact.

R50/53.- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R20/21.- Harmful by inhalation and in contact with skin.

R38.- Irritating to skin.

R10.- Flammable.

R22.- Harmful if swallowed.

R41.- Risk of serious damage to eyes.

R37/38.- Irritating to respiratory system and skin.

R67.- Vapours may cause drowsiness and dizziness.

R20.- Harmful by inhalation.

R11.- Highly flammable.

R36.- Irritating to eyes.

R66.- Repeated exposure may cause skin dryness or cracking.

R24/25.- Toxic in contact with skin and if swallowed.

R34.- Causes burns.

In case of mixing different products, labels and safety data sheets of all products must be observed .

The information contained in this safety data sheet is based on the present state of knowledge and current national and EU legislation. As the specific conditions of use of this product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

The information of the safety data sheet provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The information contained in this safety data sheet is provided in accordance with the requirements of Directive 2001/58/EEC and later adoptions and modifications.